

Compat ella®

Portable Enteral Feeding Pump

The Compat Ella® Pump is an innovative portable enteral feeding pump with a unique coloured user-friendly interface in local language.

Features at a Glance

- Continuous and interval feeding programs from 1 mL to 4000 mL, with or without dose limit
- Flow rates from 1 mL/h to 600 mL/h
- Rate and delivery progress is always visible in run mode

Easy to Learn and Understand

- A colour screen with easy to understand symbols for pump status, battery life, pump mode
- A clear U-shaped keypad with intuitive icon-based labelling
- On-screen full-text message line to convey pump status, help program nutritional therapies and **aid in problem solving**

Accurate and Safe

- Upstream and downstream occlusion alarms and air-in-line alarm
- +/- 5% delivery accuracy
- AAFF technology: Auto-Anti-Free-Flow to **promote patient safety**
- Separate delivery histories for 1) Current nutritional therapy and 2) Cumulative volume
- Keypad lock helps **avoid accidental changes**

Robust

- 5-year service interval
- Can be cleaned under warm running water

Mobile

- Lightweight and portable it can operate in any orientation
- 24-hour battery life at a delivery rate of 125 mL/h

Advanced Functions

- PDMS connection (Patient Data Management Systems)
- Interval mode delivers specific volumes at specified intervals
- Therapy lock to help **avoid accidental therapy changes**
- 30-day volume delivery history



Compat Ella® Pump Kit Contents

- Compat Ella® Pump
- AC power adapter
- Pole clamp
- Instructions for use

Compat Ella® Administration Sets

- Spike Set
- Combiset 1.5 L
- Universal Set
- Dual Spike Set

Compat Ella® Accessories

- Backpack
- Backpack Support Table Stand
- PDMS Connection Cable
- Nurse Call Connection Cable

Ordering Information

Product Name	Reference	Globe Code	Qty/Box
Compat Ella® Pump	12272020	12367032	1

Have you met Compat Ella®?

Compat Ella® Portable Enteral Feeding Pump

Pump Features

Delivery Accuracy: +/- 5%.

AAFF: Auto-Anti-Free-Flow (administration set based).

Keypad: Ergonomic U-shaped keypad with easy to identify icons.

Screen: Colour screen to highlight pump status.

Operating Languages: English, French, German, Italian, Spanish, Dutch, Swedish, Danish, Finnish, Norwegian, Czech, Slovakian, Portuguese and Polish.
User definable.

Continuous Mode: Continuous feed delivery. With or without total volume limit.

Flow Rate: 1-600 mL/h in 1 mL/h increments.

Volume Limit: 1-4000 mL in 1 mL increments.

Alarms: Air-in-line, separate upstream/downstream occlusion, door open, no cassette, end of dose, inactivity time-out, battery.

Volume This Therapy: Volume delivered for the currently active feeding nutritional therapy. User resettable.

Cumulative Volume: Total volume delivered since this parameter is reset by the user.

30-Day Volume History: Total volume delivered for each 24-hour period over the last 30 days.

Settings: Alarm volume, backlight intensity, backlight timeout, alarm at end of therapy (yes/no), keypad lock (on/off).

Priming: One touch automatic (17 mL) or manual.

Advanced Functions

Interval Mode: Delivery of specified bolus amounts in mL, at predefined intervals. Bolus from 1-2000 mL. Interval can be set from 15 minutes to 12 hours. With or without total volume limit.

Interval Mode Lockout: Interval mode is not available to the user.

Therapy Lock: Locks all the current nutritional therapy parameters so the user cannot change them.

Communication: PDMS or Nurse Call.

Date: User-adjustable date and time.

Patient Data Management System

Compat Ella® can connect to PDMS systems typically used in ICU - to allow tracking of feed delivery for individual patients in an automated manner. The physical connection is made via a custom serial cable. Specific software drivers are available upon request.

Warranty and Requirements

Warranty: 2 years.

Servicing: Only requires servicing every 5 years.

Servicing Agent: All service should be performed by authorized personnel only. Contact your Compat® representative or Compat® approved service provider.

Pump Specifications

Pump Weight: 499 g.

Battery: Li-Ion. Will run 24 hours at 125 mL/h with water. 6-Hour recharge time.

Pump Dimensions: L:140 mm x B:140 mm x H:62 mm.

Packaging: Individually packed in a box.

Storage: Store at room temperature. Keep away from sunlight and humidity.

Classification: Class IIa.

Mechanical and Fluid Ingress: IP25.

CE Mark: Complies with the European Medical Devices Directive 93/42/EEC. A CE Certification has been issued by an accredited Notified Body: TÜV SÜD.

Legal manufacturer: Axiom MTech S.A., Allée de la Petite Prairie 2, CH-1260 Nyon, Switzerland.

Country of origin: Made in Lithuania.

Compat Ella Online

Website:

www.compat.com

Training Centre:

www.compatella.com

To obtain further information please contact your Compat® representative or go to www.compat.com
®Unless stated otherwise, all trademarks are owned by Axiom MTech S.A. or used with permission.

AXI00012 REV.1 14 JANUARY 2021

Compat®